



US006120907A

United States Patent [19][11] **Patent Number:** **6,120,907****Tahon et al.**[45] **Date of Patent:** **Sep. 19, 2000**

[54] **DATA CARD COMPRISING A LASER
RECORDING MEDIUM AND A THIN GLASS
LAYER**

[75] Inventors: **Jean-Pierre Tahon**, Leuven; **Bart
Verlinden**, Boutersem; **Leo Vermeulen**,
Herenthout; **Herman Van Gorp**, Tielen,
all of Belgium

[73] Assignee: **Agfa-Gevaert, N.V.**, Morstel, Belgium

[21] Appl. No.: **09/177,505**

[22] Filed: **Oct. 23, 1998**

[30] **Foreign Application Priority Data**

Oct. 24, 1997	[EP]	European Pat. Off.	97203312
Sep. 9, 1998	[EP]	European Pat. Off. ..	PCT/EP98/05748
Sep. 22, 1998	[EP]	European Pat. Off.	98203173

[51] **Int. Cl.⁷** **B32B 3/00**

[52] **U.S. Cl.** **428/426**; 428/432; 428/433;
428/913; 430/270.12; 430/495.1; 430/945;
369/283; 369/288

[58] **Field of Search** 428/426, 432,
428/433, 688, 689, 913, 64.1, 64.4; 430/270.12,
495.1, 945; 369/283, 288

[56] **References Cited**

FOREIGN PATENT DOCUMENTS

63-074136	4/1988	Japan .
63-074137	4/1988	Japan .

Primary Examiner—Elizabeth Evans

Attorney, Agent, or Firm—Breiner & Breiner

[57] **ABSTRACT**

According to the present invention a data card is provided which comprises a heat-mode laser recording medium on a support and wherein said laser recorder medium is covered by a thin flexible glass layer. The data card has a higher mechanical strength, an improved shelf-life and offers better security with regard to counterfeiting. The heat-mode laser recording medium is preferably a metal layer of which the optical reflectivity or density can be changed by laser exposure. The glass layer is preferably a borosilicate glass having a thickness less than 850 μm .

10 Claims, No Drawings